



# TemplateMonster.com WebAPI Specification

---

A complete guide to TemplateMonster.com WebAPI provides the documentation to realize the full potential of WebAPI (Web Application Programming Interface) and covers all aspects of retrieving information about TemplateMonster.com products.

# Table of Contents

---

1. Basic concepts .....	1
2. Specification .....	2
1. Accessing TemplateMonster Catalog via HTTP .....	2
1.1. templates_screenshots4.php .....	2
1.2. template_sources.php .....	6
1.3. template_keywords.php .....	7
1.4. authors.php .....	8
1.5. categories.php .....	9
1.6. styles.php .....	11
1.7. template_categories.php .....	12
1.8. template_styles.php .....	13
1.9. featured.php .....	14
1.10. template_info3.php .....	15
1.11. template_info2.php .....	18
1.12. currency.php .....	20
1.13. templates_types.php .....	21
2. Obtaining Screenshots. ....	22
3. Checking an Order Status. ....	22
4. XML API specification. ....	23
4.1. t_info.zip. ....	23
4.2. template_updates.php. ....	27
4.3. template_xml.php. ....	29
4.4. t_info_dir.zip. ....	30
3. Versions History .....	32
4. Appendix. ....	34
1. Useful Links. ....	34
2. Links to the Shopping Cart .....	34
3. Links to Templatetuning.com .....	35

---

# Chapter 1. Basic concepts

WebAPI is a set of scripts for retrieving information about templates from TemplateMonster.com's database. It is used to get this info and store it in your own database in any form for creating your customizable template shops. It is an excellent tool for those who know a web programming language such as PHP, ASP, Perl, Coldfusion, etc. It allows a total customization of TemplateMonster.com's affiliate program - you can download all the information, screenshots, etc. to your web server and manipulate all the data in any way you please.

There are many advantages of using the WebAPI. Here's a short list of them:

- Faster, because you don't have to keep calling to TemplateMonster's servers for info.
- Easier to show the information you want your clients to view.
- The ability to have a complete control over all of the data available on TemplateMonster.com.

Data stored on your own server don't depend on TemplateMonster.com's server load and temporary traffic problems, and the most important is that you can create your custom template shop design and implement many unique features like custom search engine, etc.

Your WebAPI based template shop can be implemented in 2 ways: you can store information about templates only or all templates' data. Storing information about templates only method includes storing information about template screenshots, sources available for a particular template, keywords that describe templates, author of the template, category and style the template belongs to, templates with "featured" status assigned, etc but screenshots and flash previews of the templates are stored on the remote server [www.template-help.com](http://www.template-help.com).

Storing all the templates' data implies storing all screenshots and flash previews of the templates which requires approximately 5 GB of server space besides storing information about templates.

WebAPI scripts for getting information about templates should be invoked at least once per 24 hours. The best time to invoke them is about 8.00 AM EST. Currency rate script (`currency.php`) should be invoked once per hour.

---

# Chapter 2. Specification

## 1. Accessing TemplateMonster Catalog via HTTP

Attention: all the HTTP API scripts are password protected. In order to be able to use the scripts you need to generate a secure code (password) in your affiliate account here: <https://secure.mytemplatemonster.com/personal/webapi.php>. You have to be logged in to your affiliate account in order to access this page.

You should add the secure password after request using the & for example:

```
ht-tp://www.templatemonster.com/webapi/templates_screenshots4.php?delim=|&from=12&to=30&keyword=hostin&sort_by=price&currency=EUR&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86
```

Please do not use the password for your templates shop as this is just a sample.

### 1.1. templates\_screenshots4.php

#### URL:

[http://www.templatemonster.com/webapi/templates\\_screenshots4.php](http://www.templatemonster.com/webapi/templates_screenshots4.php)

#### Description:

Returns a plain text table of properties of selected templates.

#### Status:

0.2

#### Synopsis:

```
ht-tp://www.templatemonster.com/webapi/templates_screenshots4.php?[linebreak=<linebreak>][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number> | &last_added=Yes | &sold=Yes][&filter=<filter_number>] [&category=<category_number>] [&keywords=<keywords>] [&sort_by=<sort_type>] [&order=( asc | desc )] [&list_delim=<delimiter>] [&list_begin=<list_begin_char>] [&list_end=<list_end_char>] [&full_path=<full_path_flag>][&currency=<currency>]
```

#### Parameters:

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate lines (default: \r\n)
delim	string	a sequence of characters used to separate columns (default: \t)
from	integer	a starting template number (inclusive, default: 1)
to	integer	an ending template number (inclusive, default: a maximum item number available)
last_added=Yes	string	Templates from the last 'new templates report' will be listed only if this parameter exists and has a nonzero length.
sold=Yes	string	Sold and permanently removed

Parameter	Type	Description
		from TemplateMonster templates will be listed only if this parameter exists and has a nonzero length.
filter	integer	<p>If this parameter exists, not all templates will be returned, but the ones that match certain criteria (default: 0). Acceptable values:</p> <ul style="list-style-type: none"> <li>• 0 - all templates except adult website templates</li> <li>• 1 - website templates only (hosting website templates included)</li> <li>• 2 - hosting website templates only</li> <li>• 3 - flash intro templates only</li> <li>• 4 - adult website templates only</li> <li>• 5 - unique logo templates only</li> <li>• 6 - non unique logo templates only</li> <li>• 7 - unique corporate identity packages only</li> <li>• 8 - non-unique corporate identity packages only.</li> </ul>
keywords	string	A space separated list of keywords associated with the template. If this parameter exists, not all templates will be returned but the ones that contain given keywords only.
category	integer	If this parameter exists, not all templates will be returned, but the ones that belong to this category only. Use a script categories.php to obtain acceptable values.
sort_by	string	If this parameter exists, records will

Parameter	Type	Description
		<p>be sorted by a certain attribute. By default, records are sorted by a template number. Acceptable values:</p> <ul style="list-style-type: none"> <li>• <i>number</i> - sort by a template number</li> <li>• <i>date</i> - sort by date of addition</li> <li>• <i>price</i> - sort by price</li> </ul>
order=( asc   desc )	string	<p>The default order is ascending. Acceptable values:</p> <ul style="list-style-type: none"> <li>• <i>asc</i> - ascending order</li> <li>• <i>desc</i> - descending order</li> </ul>
list_delim	string	a sequence of characters used to separate list items (default: , )
list_begin	string	a sequence of characters used to mark the beginning of the list (default: { )
list_end	string	a sequence of characters used to mark the end of the list (default: } )
full_path	string	if this parameter exists and its value is 'true' a full path to screenshots is returned.
currency	3 chars	<p>If this parameter exists templates prices will be priced using a currency different from USD. Acceptable values:</p> <ul style="list-style-type: none"> <li>• <i>EUR</i> - templates prices will be in Euros</li> <li>• <i>CAD</i> - templates prices will be in Canadian Dollars</li> <li>• <i>GBP</i> - templates prices will be in British Pounds Sterling</li> <li>• <i>JPY</i> - templates prices will be in Japanese Yen</li> </ul>

Parameter	Type	Description
		<ul style="list-style-type: none"> <li>AUD -templates prices will be in Australian Dollars.</li> </ul>

**Response:**

Response is a plain text table delimited with <delimiter>. It consists of the following columns (without columns headers):

Column	Type	Description
id	integer	an item number of the template
price	integer	a regular price of the template
exclusive price	integer	an exclusive price of the template
date of addition	date	the date when the template was added to the database in YYYY-MM-DD format
number of downloads	integer	the number of downloads
is hosting	integer (1/0) 1-true	equals 1 for Hosting Website templates
is flash	integer (1/0) 1-true	equals 1 for Flash Intro templates
is adult	integer (1/0) 1-true	equals 1 for Adult templates
is unique logo	integer (1/0) 1-true	equals 1 for unique Logo templates
is non unique logo	integer (1/0) 1-true	equals 1 for non-unique Logo templates
is unique corporate	integer (1/0) 1-true	equals 1 for unique Corporate Identity Packages
is non unique corporate	integer (1/0) 1-true	equals 1 for non-unique Corporate Identity Packages
author's ID	integer	a template's author identifier
is full site template	integer (1/0) 1-true	equals 1 for Full Site templates
number of pages	integer	the number of subpages (some templates are not full site templates but still contain several subpages).
screenshots list	list	a list of all screenshots of this template delimited with <delimiter>, started with <list_begin> and ended with <list_end>. By default, only variable part of URL is displayed. If you want to obtain a full URL, set <full_path> parameter to 'true'

**Response example:(please do not use this password for your templates shop)**

ht-

tp://www.templatemonster.com/webapi/templates\_screenshots4.php?delim=|&from=12&to=30&keyword=hosting&sort\_by=price&currency=EUR&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtr86

```
19|10.59|174.74|2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/19-b.jpg,0/19-h.jpg,0/19-m.jpg,0/19-rs.jpg}|
25|12.36|144.73|2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/25-b.jpg,0/25-h.jpg,0/25-m.jpg,0/25-rs.jpg}|
12|13.24|138.55|2002-05-01|5|0|0|0|0|0|0|1|0|0|{0/12-b.jpg,0/12-h.jpg,0/12-m.jpg}|
13|13.24|138.55|2002-05-01|9|0|0|0|0|0|0|1|0|0|{0/13-b.jpg,0/13-h.jpg,0/13-m.jpg}|
```

```

15|13.24|112.08|2002-05-01|4|0|0|0|0|0|0|0|1|0|0|{0/15-b.jpg,0/15-h.jpg,0/15-m.jpg}
17|13.24|181.80|2002-05-01|8|0|0|0|0|0|0|0|1|0|0|{0/17-b.jpg,0/17-h.jpg,0/17-m.jpg}
27|13.24|131.49|2002-05-01|5|0|0|0|0|0|0|0|1|0|0|{0/27-b.jpg,0/27-h.jpg,0/27-m.jpg,0/27-rs.jpg}
21|15.00|157.97|2002-05-01|6|0|0|0|0|0|0|0|1|0|0|{0/21-b.jpg,0/21-h.jpg,0/21-m.jpg,0/21-rs.jpg}
29|15.00|122.67|2002-05-01|5|0|0|0|0|0|0|0|1|0|0|{0/29-b.jpg,0/29-h.jpg,0/29-m.jpg,0/29-rs.jpg}
18|17.65|166.79|2002-05-01|3|0|0|0|0|0|0|0|1|0|0|{0/18-b.jpg,0/18-h.jpg,0/18-m.jpg,0/18-rs.jpg}
23|21.18|184.44|2002-05-01|5|0|0|0|0|0|0|0|1|0|0|{0/23-b.jpg,0/23-h.jpg,0/23-m.jpg,0/23-rs.jpg}
26|21.18|215.33|2002-05-01|4|0|0|0|0|0|0|0|1|0|0|{0/26-b.jpg,0/26-h.jpg,0/26-m.jpg,0/26-rs.jpg}
16|25.59|157.97|2002-05-01|4|0|0|0|0|0|0|0|1|0|0|{0/16-b.jpg,0/16-h.jpg,0/16-m.jpg}
28|25.59|224.16|2002-05-01|5|0|0|0|0|0|0|0|1|0|0|{0/28-b.jpg,0/28-h.jpg,0/28-m.jpg}

```

## 1.2. template\_sources.php

### URL:

[http://www.templatemonster.com/webapi/template\\_sources.php](http://www.templatemonster.com/webapi/template_sources.php)

### Description:

Returns a plain text table of sources available for templates.

### Status:

0.1

### Synopsis:

`http://www.templatemonster.com/webapi/template_sources.php?[linebreak=<linebreak>][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number>]`

### Parameters:

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)
from	integer	an item number of the first template (inclusive, default: 1)
to	integer	an item number of the last template (inclusive, default: a maximum item number available)

### Response:

Response is a plain text table delimited with <delimiter>. The table contains information about available sources for templates from <first\_template\_number> to <last\_template\_number> (inclusive). It consists of the following columns (without columns headers):

Column	Type
id	integer
sources	string

### Response example:

*ht-*

[tp://www.templatemonster.com/webapi/template\\_sources.php?from=8888&to=8899&login=kara&webapipasswo rd=23kikhuh8656io62549hjsdguwtre86](http://www.templatemonster.com/webapi/template_sources.php?from=8888&to=8899&login=kara&webapipasswo rd=23kikhuh8656io62549hjsdguwtre86)

```
8888 .PSD; .HTML;
8889 .FLA; .SWF; .PSD; .HTML;
8890 .FLA; .SWF; .PSD; .HTML;
8891 .PSD; .HTML; .FLA; .SWF;
8892 .PSD; .SWF; .FLA; .HTML;
8893 .FLA; .SWF; .PSD; .HTML;
8894 .FLA; .SWF; .PSD; .HTML;
8895 .SWF; .FLA; .PSD; .HTML;
8896 .PSD; .HTML;
8897 .PSD; .HTML;
8898 .PSD; .HTML;
8899 .FLA; .SWF; .PSD; .HTML;
```

## 1.3. template\_keywords.php

### URL:

[http://www.templatemonster.com/webapi/template\\_keywords.php](http://www.templatemonster.com/webapi/template_keywords.php)

### Description:

Returns a plain text table of keywords associated with templates. Attention: the script is password protected. In order to be able to use the script you need to generate a secure code (password) in your affiliate account here: <https://secure.mytemplatestorage.com/personal/webapi.php>. You have to be logged in to your affiliate account in order to access this page.

### Status:

0.1

### Synopsis:

[http://www.templatemonster.com/webapi/template\\_keywords.php?\[\linebreak=<linebreak>\]\[&delim=<delimiter>\]\[&from=<first\\_template\\_number>&to=<last\\_template\\_number>\]](http://www.templatemonster.com/webapi/template_keywords.php?[\linebreak=<linebreak>][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number>])

### Parameters:

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)
from	integer	an item number of the first template (inclusive, default: 1)
to	integer	an item number of the last template (inclusive, default: a maximum item number available)

### Response:

Response is a plain text table delimited with <delimiter>. The table contains information about keywords associated with templates from <first\_template\_number> to <last\_template\_number> (inclusive). It consists of the following columns (without columns headers):

Column	Type
id	integer
keywords	a string of keywords separated by spaces

**Response example:**

ht-

tp://www.templatemonster.com/webapi/template\_keywords.php?from=900&to=915&login=kara&webapipasswor  
d=23kikhuh8656io62549hjsdguwtre86

```

900 | music mp3 songs singers bands audio
901 | cars driving speed highway road automobiles vehicles
902 | creative webdesign webpage website butterfly
903 | hosting servers traffic domain bandwidth notebook
905 | mobile phones cellular communication communications phone
908 | furniture company interior design studio
909 | computers it computer retailer internet media communication communications
910 | bank banking insurance credit credits finance financing stock exchange money
911 | hosting servers traffic domain bandwidth
912 | flash intro business
914 | internet auction bids vendue clocks
915 | domain registration domain name web address web hosting hosting host

```

## 1.4. authors.php

**URL:**

http://www.templatemonster.com/webapi/authors.php

**Description:**

Returns a plain text table of all authors' IDs and nicknames.

**Status:**

0.1

**Synopsis:**

http://www.templatemonster.com/webapi/authors.php?[[linebreak=<linebreak>]][&delim=<delimiter>]

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about the authors. It consists of the following columns (without columns headers):

Column	Type
author's ID	integer

Column	Type
author's nickname	string

**Response example:**

ht-

tp://www.templatemonster.com/webapi/authors.php?delim=|&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86

```

1 | Big mama
3 | Engine
4 | MariArti
5 | Casher
10 | Dipixel
12 | MAN!AK
13 | Pharaoh
14 | Dan
15 | SR
17 | Sloth
18 | Bullet
19 | Orange
21 | Mc Oyed
22 | Hummingbird
24 | Wolf
25 | Photographer
26 | Shrew
27 | Dgan Dgan
30 | Glasgo Ranger
32 | Flayer
36 | Co-casher
37 | Mr. Corpuscle

```

## 1.5. categories.php

**URL:**

http://www.templatemonster.com/webapi/categories.php

**Description:**

Returns a table of all templates categories

**Status:**

0.2

**Synopsis:**

ht-

tp://www.templatemonster.com/webapi/categories.php?[[linebreak=<linebreak>]][&delim=<delimiter>]][locale=<locale>]

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)

Parameter	Type	Description
locale	string	2 characters on locales name (default: en) Acceptable values: <ul style="list-style-type: none"><li>• <i>cz</i> - Czech</li><li>• <i>en</i> - English</li><li>• <i>de</i> - German</li><li>• <i>dk</i> - Danish</li><li>• <i>du</i> - Dutch</li><li>• <i>es</i> - Spanish</li><li>• <i>fi</i> - Finnish</li><li>• <i>fr</i> - French</li><li>• <i>hu</i> - Hungarian</li><li>• <i>it</i> - Italian</li><li>• <i>pl</i> - Polish</li><li>• <i>pt</i> - Portuguese</li><li>• <i>ro</i> - Romanian</li><li>• <i>tr</i> - Turkish</li></ul>

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about templates categories. It consists of the following columns (without columns headers):

Column	Type
id of category	integer
name of category	string

**Response example:**

ht-

tp://www.templatemonster.com/webapi/categories.php?locale=de&delim=|&login=kara&webapipassword=23kik  
huuh8656io62549hjsdguwtre86

```

1 | Beauty
2 | Business
3 | Computer
4 | Immobilien
5 | Portal
6 | Internet
7 | Familie
8 | Webdesign
9 | Unterhaltung
10 | Medizin
11 | Auto
13 | Neutral
14 | Sport
16 | Industrie
17 | Religion
18 | Medien
19 | Musik

```

## 1.6. styles.php

**URL:**

<http://www.templatemonster.com/webapi/styles.php>

**Description:**

Returns a table of all templates styles

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/styles.php?\[linebreak=<linebreak>\]\[&delim=<delimiter>\]](http://www.templatemonster.com/webapi/styles.php?[linebreak=<linebreak>][&delim=<delimiter>])

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about templates styles.

It consists of the following columns (without columns headers):

Column	Type
id of style	integer
name of style	string

**Response example:**

```
ht-
tp://www.templatemonster.com/webapi/styles.php?delim=|&login=kara&webapipassword=23kikhuh8656io6254
9hjsdguwtre86
```

```
1 | 3d
2 | Artworks
3 | Cartoon
4 | Clean
5 | Collage
6 | Dark
7 | Futurist
8 | Geometric
9 | Grunge
10 | Minimalist
11 | Paper Made
12 | Retro
13 | Corporate
14 | Urban / Street
15 | Vector
16 | Neutral
```

## 1.7. template\_categories.php

**URL:**

[http://www.templatemonster.com/webapi/template\\_categories.php](http://www.templatemonster.com/webapi/template_categories.php)

**Description:**

Returns a plain text table that is a sequence of templates numbers and corresponding categories names. Warning: a template can belong to many categories, so more than one line can contain this template id.

**Status:**

0.1

**Synopsis:**

```
http://www.templatemonster.com/webapi/template_categories.php?[[linebreak=<linebreak>]][&delim=<delimiter>]
[&from=<first_template_number>&to=<last_template_number>]
```

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)
from	integer	an item number of the first template (inclusive, default: 1)

Parameter	Type	Description
to	integer	an item number of the last template (inclusive, default: a maximum item number available at <a href="http://templatemonster.com">templatemonster.com</a> )

**Response:**

Response is a plain text table delimited with `<delimiter>`. The table contains information about categories content for templates from `<first_template_number>` to `<last_template_number>` (inclusive). It consists of the following columns (without columns headers):

Column	Type
id of template	integer
id of category	integer

**Response example:**

ht-

[tp://www.templatemonster.com/webapi/template\\_categories.php?delim=|&from=9005&to=9008&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86](http://www.templatemonster.com/webapi/template_categories.php?delim=|&from=9005&to=9008&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86)

```
9005 | 42
9005 | 50
9005 | 63
9005 | 83
9005 | 84
9006 | 42
9006 | 50
9006 | 63
9006 | 83
9006 | 84
9007 | 40
9007 | 66
9007 | 68
9008 | 27
9008 | 68
```

## 1.8. template\_styles.php

**URL:**

[http://www.templatemonster.com/webapi/template\\_styles.php](http://www.templatemonster.com/webapi/template_styles.php)

**Description:**

Returns a plain text table that is a sequence of templates numbers and corresponding styles IDs. Warning: a template can belong to many styles, so more than one line can contain this template id.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/template\\_styles.php?\[\[linebreak=<linebreak>\]\]\[&delim=<delimiter>\]\[&from=<first\\_template\\_number>&to=<last\\_template\\_number>\]](http://www.templatemonster.com/webapi/template_styles.php?[[linebreak=<linebreak>]][&delim=<delimiter>][&from=<first_template_number>&to=<last_template_number>])

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)
from	integer	an item number of the first template (inclusive, default: 1)
to	integer	an item number of the last template (inclusive, default: a maximum item number available at <a href="http://templatemonster.com">templatemonster.com</a> )

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about styles content for templates from <first\_template\_number> to <last\_template\_number> (inclusive). It consists of the following columns (without columns headers):

Column	Type
id of template	integer
id of style	integer

**Response example:**

ht-

[tp://www.templatemonster.com/webapi/template\\_styles.php?delim=|&from=9002&to=9008&login=kara&webapi\\_password=23kikhuuh8656io62549hjsdguwtre86](http://www.templatemonster.com/webapi/template_styles.php?delim=|&from=9002&to=9008&login=kara&webapi_password=23kikhuuh8656io62549hjsdguwtre86)

```
9002 | 5
9003 | 2
9003 | 5
9003 | 16
9004 | 16
9005 | 4
9005 | 16
9006 | 4
9007 | 5
9007 | 9
9008 | 16
```

## 1.9. featured.php

**URL:**

<http://www.templatemonster.com/webapi/featured.php>

**Description:**

Returns a list of the numbers of featured templates. There are two types of featured templates: featured website templates and featured flash intro templates. You can review featured website templates at <http://www.templatemonster.com/index.php> and featured flash intro templates at <http://www.templatemonster.com/flash-templates.php>

**Status:**

0.1

**Synopsis:**

`http://www.templatemonster.com/webapi/featured.php?[linebreak=<linebreak>][&delim=<delimiter>] [&type= (website | flash )]`

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)
type	string	a type of featured templates. Acceptable values: website or flash. The default value is website.

**Response:**

Response is a plain text string containing template numbers delimited with <delimiter>.

**Response example:**

ht-  
tp://www.templatemonster.com/webapi/featured.php?delim=|&type=flash&login=kara&webapipassword=23kikhu  
uh8656io62549hjsdguwtre86

9634 | 9426 | 8669 | 9635

## 1.10. template\_info3.php

**URL:**

`http://www.templatemonster.com/webapi/template_info3.php`

**Description:**

Returns the info about the selected template.

**Status:**

0.2

**Synopsis:**

`http://www.templatemonster.com/webapi/template_info.php?[linebreak=<linebreak>][&delim=<delimiter>]  
[&template_number=<template_number>] [&list_delim=<delimiter>] [&list_begin=<list_begin_char>]  
[&list_end=<list_end_char>]`

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)

Parameter	Type	Description
template_number	integer	an item number of the template (default: 1)
list_delim	string	a sequence of characters used to separate list items (default: , )
list_begin	string	a sequence of characters used to mark the beginning of the list (default: { )
list_end	string	a sequence of characters used to mark the end of the list (default: } )

**Response:**

Response is a plain text table delimited with <delimiter>. It consists of the following columns (without columns headers):

Column	Type	Description
id	integer	an item number of the template
price	integer	a template price (in USD)
exclusive price	integer	an exclusive price of the template (in USD)
date of addition	date	date of addition in YYYY-MM-DD format
number of downloads	integer	the number of downloads
is hosting	integer (1/0) 1-true	1 for Hosting Website templates
is flash	integer (1/0) 1-true	1 for Flash Intro templates
is adult	integer (1/0) 1-true	1 for Adult templates
is unique logo	integer (1/0) 1-true	1 for unique Logo templates
is non unique logo	integer (1/0) 1-true	1 for non-unique Logo templates
is unique corporate	integer (1/0) 1-true	1 for unique Corporate Identity Packages
is non unique corporate	integer (1/0) 1-true	1 for non-unique Corporate Identity Packages
author's ID	integer	a template's author identifier
author's nick	string	a template's author nickname
is full site template	integer (1/0) 1-true	1 for Full Site templates
is Real Size	integer (1/0) 1-true	1 if "Real Size" screenshot exists
screenshots list	list	the list of all screenshots of this template separated by <delimiter>, started with <list_begin> and ended with <list_end>. Full URL is displayed.
keywords list	list	a list of all keywords associated with the template separated by<delimiter> starting with <list_begin> and ending with <list_end>.
categories list (Identifiers)	list	a list of all category identifiers of this template separated by <delimiter> starting with <list_begin> and end-

Column	Type	Description
		ing with <list_end>.
categories list (names)	list	a list of all category names of this template separated by <delimiter> starting with <list_begin> and ending with <list_end>.
sources	string	information about sources available for this template starting with <list_begin> and ending with <list_end>.
package	string	template package starting with <list_begin> and ending with <list_end>.
description	string	a description of this template starting with <list_begin> and ending with <list_end>.
pages	list	a list of all pages of this template starting with <list_begin> and ending with <list_end>. Each page consists of the page name (starting with <list_begin> and ending with <list_end>) and the list of screenshots (starting with <list_begin> and ending with <list_end>). Each screenshot consists of the screenshot name (starting with <list_begin> and ending with <list_end>) and the screenshot URL (starting with <list_begin> and ending with <list_end>). Full URL is displayed.
type	string	a type of the template starting with <list_begin> and ending with <list_end>.

**Response example:**

ht-

tp://www.templatemonster.com/webapi/template\_info3.php?delim=|&template\_number=22568&list\_delim=:&list\_begin=|&list\_end=|&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86

```
22568,63,2300,2008-12-30,3,0,0,0,0,0,0,183,Glenn,0,0,[],[],[],[ .PSD; .HTML],[CSS STATIC FULL
SITE],[],[[[Homepage]][[ADOBE PHOTOSHOP HOMEPAGE SCREEN-
SHOT][http://templatemonster.dev/screenshots/22500/22568-b.jpg]][[HTML HOMEPAGE SCREEN-
SHOT][http://templatemonster.dev/screenshots/22500/22568-h.jpg]][[Company]][[PHOTOSHOP CONTENT
PAGE SCREENSHOT][http://templatemonster.dev/screenshots/22500/22568-1-b.jpg]][[ HTML CONTENT
PAGE SCREEN-
SHOT][http://templatemonster.dev/screenshots/22500/22568-1-sph.jpg]][[Services]][[PHOTOSHOP CONTENT
PAGE SCREENSHOT][http://templatemonster.dev/screenshots/22500/22568-2-b.jpg]][[HTML CONTENT PAGE
SCREENSHOT][http://templatemonster.dev/screenshots/22500/22568-2-sph.jpg]][[Solutions]][[PHOTOSHOP
CONTENT PAGE SCREENSHOT][http://templatemonster.dev/screenshots/22500/22568-3-b.jpg]][[HTML CON-
TENT PAGE SCREEN-
SHOT][http://templatemonster.dev/screenshots/22500/22568-3-sph.jpg]][[Contacts]][[PHOTOSHOP CONTENT
PAGE SCREENSHOT][http://templatemonster.dev/screenshots/22500/22568-4-b.jpg]][[HTML CONTENT PAGE
SCREENSHOT][http://templatemonster.dev/screenshots/22500/22568-4-sph.jpg]][[Privacy
Policy]][[PHOTOSHOP CONTENT PAGE SCREEN-
SHOT][http://templatemonster.dev/screenshots/22500/22568-5-b.jpg]][[HTML CONTENT PAGE SCREEN-
```

SHOT][<http://templatemonster.dev/screenshots/22500/22568-5-sph.jpg>]]],[Website Templates],

## 1.11. template\_info2.php

### URL:

[http://www.templatemonster.com/webapi/template\\_info2.php](http://www.templatemonster.com/webapi/template_info2.php)

### Description:

Returns the info about the selected template.

### Status:

0.2

### Synopsis:

[http://www.templatemonster.com/webapi/template\\_info.php?\[%linebreak=<linebreak>\]\[%delim=<delimiter>\]\[%template\\_number=<template\\_number>\]\[%list\\_delim=<delimiter>\]\[%list\\_begin=<list\\_begin\\_char>\]\[%list\\_end=<list\\_end\\_char>](http://www.templatemonster.com/webapi/template_info.php?[%linebreak=<linebreak>][%delim=<delimiter>][%template_number=<template_number>][%list_delim=<delimiter>][%list_begin=<list_begin_char>][%list_end=<list_end_char>)

### Parameters:

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)
template_number	integer	an item number of the template (default: 1)
list_delim	string	a sequence of characters used to separate list items (default: , )
list_begin	string	a sequence of characters used to mark the beginning of the list (default: { )
list_end	string	a sequence of characters used to mark the end of the list (default: } )

### Response:

Response is a plain text table delimited with <delimiter>. It consists of the following columns (without columns headers):

Column	Type	Description
id	integer	an item number of the template
price	integer	a template price (in USD)
exclusive price	integer	an exclusive price of the template (in USD)
date of addition	date	date of addition in YYYY-MM-DD format
number of downloads	integer	the number of downloads
is hosting	integer (1/0) 1-true	1 for Hosting Website templates
is flash	integer (1/0) 1-true	1 for Flash Intro templates

Column	Type	Description
is adult	integer (1/0) 1-true	1 for Adult templates
is unique logo	integer (1/0) 1-true	1 for unique Logo templates
is non unique logo	integer (1/0) 1-true	1 for non-unique Logo templates
is unique corporate	integer (1/0) 1-true	1 for unique Corporate Identity Packages
is non unique corporate	integer (1/0) 1-true	1 for non-unique Corporate Identity Packages
author's ID	integer	a template's author identifier
author's nick	string	a template's author nickname
is full site template	integer (1/0) 1-true	1 for Full Site templates
is Real Size	integer (1/0) 1-true	1 if "Real Size" screenshot exists
screenshots list	list	the list of all screenshots of this template separated by <delimiter>, started with <list_begin> and ended with <list_end>. Full URL is displayed.
keywords list	list	a list of all keywords associated with the template separated by<delimiter> starting with <list_begin> and ending with <list_end>.
categories list (Identifiers)	list	a list of all category identifiers of this template separated by <delimiter> starting with <list_begin> and ending with <list_end>.
categories list (names)	list	a list of all category names of this template separated by <delimiter> starting with <list_begin> and ending with <list_end>.
sources	string	information about sources available for this template starting with <list_begin> and ending with <list_end>.
package	string	template package starting with <list_begin> and ending with <list_end>.
description	string	a description of this template starting with <list_begin> and ending with <list_end>.
pages	list	a list of all pages of this template starting with <list_begin> and ending with <list_end>. Each page consists of the page name (starting with <list_begin> and ending with <list_end>) and the list of screenshots (starting with <list_begin> and ending with <list_end>). Each screenshot consists of the screenshot name (starting with <list_begin> and ending with <list_end>) and the screenshot URL (starting with <list_begin> and ending with <list_end>). Full URL is displayed.

**Response example:**

```

ht-
tp://www.templatemonster.com/webapi/template_info2.php?delim=|&template_number=9005&list_delim=;&list_
begin=[&list_end=]&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86

9005|174|6960|2005-08-11|6|0|0|0|0|0|0|150|Monet|0|1|[http://images.templatemonster.com/screenshots/9000
/9005-banner.jpg;
ht-
tp://images.templatemonster.com/screenshots/9000/9005-html.html;http://images.templatemonster.com/screens
hots/9000/9005-m.jpg;
http://images.templatemonster.com/screenshots/9000/9005-osc-b.jpg;
ht-
tp://images.templatemonster.com/screenshots/9000/9005-rs.jpg]
[shop;hardware;accessory;broadband;laptop;notebook;changer;stereo;system;player;computer;camera;phone;
mobile;cellular;cable;CD;DVD;
CD-
RW;desktop;printer;Xerox;HP;monitor;barebone;mice;input;device;memory;server;wireless;MP3;player][42;50;6
3;83;84][Online store/shop;Electronics;Clean style;Most Popular;osCommerce Templates][.PSD; .PHP][OS
commerce 2.2][OsCommerce Templates are ready made solutions to use for on-line shops. OsCommerce
Template is actually a combination of osCommerce 2.2 (ready made on-line shop) provided by osCom-
merce.com and the original osCommerce design. ][[[Homepage][REAL SIZE SCREEN-
SHOT][http://images.templatemonster.com/screenshots/9000/9005-rs.jpg]]
[[[http://images.templatemonster.com/screenshots/9000/9005-html.html]] [[OSCommerce Main Page pre-
view][http://images.templatemonster.com/screenshots/9000/9005-osc-b.jpg]]]]]

```

## 1.12. currency.php

**URL:**

<http://www.templatemonster.com/webapi/currency.php>

**Description:**

Returns a table of currency exchange rates.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/currency.php?linebreak=<linebreak>\[&delim=<delimiter>\]](http://www.templatemonster.com/webapi/currency.php?linebreak=<linebreak>[&delim=<delimiter>)

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about currency exchange rates. It consists of the following columns (without columns headers):

Column	Type
id of the currency	integer
name of the currency	string
exchange rate of the currency	float

**Response example:**

ht-

tp://www.templatemonster.com/webapi/currency.php?delim=|&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86

```
1 | EUR | 0.882503
2 | CAD | 1.21932
3 | GBP | 0.609381
4 | JPY | 127.203
5 | AUD | 1.4079
```

## 1.13. templates\_types.php

**URL:**

http://www.templatemonster.com/webapi/templates\_types.php

**Description:**

Returns a table of template types.

**Status:**

0.1

**Synopsis:**

http://www.templatemonster.com/webapi//templates\_types.php?[linebreak=<linebreak>][&delim=<delimiter>]

**Parameters:**

Parameter	Type	Description
linebreak	string	a sequence of characters used to separate the lines (default: \r\n)
delim	string	a sequence of characters used to separate the columns (default: \t)

**Response:**

Response is a plain text table delimited with <delimiter>. The table contains information about template types. It consists of the following columns (without columns headers):

Column	Type
id of the type	integer
description of type	string

**Response example:**

ht-

tp://www.templatemonster.com/webapi/templates\_types.php?delim=|&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86

```
1 Website Templates
3 Flash Intro Templates
5 Logo Templates
```

6 Non-unique Logo Templates  
 7 Corporate Identity  
 8 Non-unique Corporate Identity  
 9 Flash Templates  
 10 PHP-Nuke Templates  
 11 Logosets  
 12 Icon Sets  
 13 SWiSH Templates  
 14 osCommerce Templates  
 15 PhpBB Templates  
 16 ZenCart Templates  
 17 WordPress Themes  
 18 CRE Loaded Templates  
 19 Dynamic Flash Photo Galleries  
 24 Joomla Templates  
 25 Mambo Templates  
 26 Drupal Templates  
 27 Magento Themes

## 2. Obtaining Screenshots.

Use a script templates\_screenshots4.php to get the list of screenshots URLs for a particular template.

For example, we can obtain a list of screenshots for a template number 1000 using [http://www.templatemonster.com/webapi/templates\\_screenshots4.php?from=20000&to=20000](http://www.templatemonster.com/webapi/templates_screenshots4.php?from=20000&to=20000) Then we can add the variable part of the URL to templatemonster.com domain name and download the screenshot using an URL: <http://www.templatemonster.com/screenshots/20000/20000-m.jpg>

## 3. Checking an Order Status.

### URL:

[http://www.templatemonster.com/webapi/order\\_status.php](http://www.templatemonster.com/webapi/order_status.php)

### Description:

Returns the status of the requested order

### Status:

0.1

### Synopsis:

[http://www.templatemonster.com/webapi/order\\_status.php?order\\_id=<templatemonster\\_order\\_id>](http://www.templatemonster.com/webapi/order_status.php?order_id=<templatemonster_order_id>)

### Parameters:

Parameter	Type	Description
templatemonster_order_id	string( 20 chars length)	TemplateMonster order identifier

### Response:

Response is a string containing a single word which describes a current status of the requested order:

Value	Description
Attempt	an order has not been paid for yet

Value	Description
Bought	successful purchase
Fraud	transaction was cancelled
Wrong	there is no order associated with a specified order ID in the database

**Response example:**

ht-  
[tp://www.templatemonster.com/webapi/order\\_status.php?order\\_id=7oyH4IMR78hxHaAv43hZ&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86](http://www.templatemonster.com/webapi/order_status.php?order_id=7oyH4IMR78hxHaAv43hZ&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86)

Fraud

## 4. XML API specification.

Attention: XML API scripts `template_updates.php` and `template_xml.php` are password protected. In order to be able to use the scripts you need to generate a secure code (password) in your affiliate account here: <https://secure.mytemplatestorage.com/personal/webapi.php>. You have to be logged in to your affiliate account in order to access this page.

You should add the secure password after request using the `&` for example:

ht-  
[tp://www.templatemonster.com/webapi/template\\_xml.php?template\\_number=12125&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86](http://www.templatemonster.com/webapi/template_xml.php?template_number=12125&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86)

Please do not use the password for your templates shop as this is just a sample.

Download complete information about all templates in a single zipped XML file: [http://www.templatemonster.com/webapi/xml/t\\_info.zip](http://www.templatemonster.com/webapi/xml/t_info.zip)

### 4.1. t\_info.zip.

**URL::**

[http://www.templatemonster.com/webapi/xml/t\\_info.zip](http://www.templatemonster.com/webapi/xml/t_info.zip)

**Description:**

Download complete information about all templates in a single zipped XML file.

**Status:**

0.1

**Synopsis:**

[http://www.templatemonster.com/webapi/xml/t\\_info.zip](http://www.templatemonster.com/webapi/xml/t_info.zip)

**Parameters:**

No

**Response:**

XML file contains an XML-encoded array. The array consists of the following arrays:

Field	Type	Description
id	integer	an item number of the template
state	integer	equals 0 for hidden templates. Equals 1 for visible templates. Equals 2 for exclusively sold templates.
price	integer	a regular price of the template (in USD)
exc_price	integer	an exclusive price of the template (in USD)
inserted_date	date	date of addition in YYYY-MM-DD format
downloads	integer	the number of downloads
template_type	string	a type of the template
update_date	date	The date of the latest update in the format YYYY-MM-DD hh:mm:ss
is_flash	integer (1/0) 1-true	1 for Flash Intro templates
is_adult	integer (1/0) 1-true	1 for Adult templates
<width>980px</width>		Width of the template in pixels
sources_available_list	array	The list of IDs corresponding to the node <sources></sources> of the directories archive t_info_dir.zip. The list contains IDs of the source formats included into redistributable package of the template.
screenshots_list	array	An array of all the screenshots and time of the screenshot modification. Full URL is displayed. Contains small_preview and main_preview arrays that have the 1 value for the screenshots of the small template preview and main template preview (the image showing on roll-over) accordingly.
software_required_list	array	The list of IDs corresponding to the node <softwares></softwares> of the directories archive t_info_dir.zip. The list contains IDs of the software needed for editing and changing sources of the template.
author	integer	a template author
is_full_site	integer (1/0) 1-true	1 for Full Site templates
is_real_size	integer (1/0) 1-true	1 if a "Real Size" screenshot exists
screenshots_list	array	an array of all screenshots and screenshots file modification time. Full URL is displayed.
keywords	string	a list of all keywords associated with a particular template (space separated).

Field	Type	Description
styles	array	an array of all styles of a particular template
categories	array	an array of all categories of a particular template
sources	string	information about sources available for this template( deprecated).
description	string	a description of the template.
software_required	string	a software required for editing the template (deprecated).
pages	array	an array of all pages of the template. Each page consists of the name of the page and the list of screenshots. Each screenshot consists of the screenshot name and the URL. Full URL is displayed.
packages	int	The number of the package to which the template belongs.

**Response example:**

```
<?xml version="1.0" encoding="utf-8" ?>
<templates>
  <template id="21000">
    <id>21000</id>
    <state>1</state>
    <price>140</price>
    <exc_price>1100</exc_price>
    <inserted_date>2008-09-15 05:15:02</inserted_date>
    <update_date>2008-10-15 04:33:57</update_date>
    <downloads>0</downloads>
    <template_type>
      <type_id>16</type_id>
      <type_name>ZenCart Templates</type_name>
    </template_type>
    <is_flash>0</is_flash>
    <is_adult>0</is_adult>
    <width>766px</width>
    <author>
      <author_id>85</author_id>
      <author_nick>Delta</author_nick>
    </author>
    <package>
      <package_id>132</package_id>
    </package>
    <is_full_site>0</is_full_site>
    <is_real_size>1</is_real_size>
    <screenshots_list>
      <screenshot>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-banner.jpg</uri>
        <filemtime>2008-08-28 08:08:20</filemtime>
      </screenshot>
      <screenshot>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-m.jpg</uri>
        <filemtime>2008-08-28 08:08:20</filemtime>
        <small_preview>1</small_preview>
      </screenshot>
      <screenshot>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-rs.jpg</uri>
        <filemtime>2008-08-28 08:08:20</filemtime>
      </screenshot>
    </screenshots_list>
  </template>
</templates>
```

```
</screenshot>
<screenshot>
  <uri>http://images.templatemonster.com/screenshots/21000/21000-z-b.jpg</uri>
  <filemtime>2008-08-28 08:08:20</filemtime>
  <main_preview>1</main_preview>
</screenshot>
<screenshot>
  <uri>http://images.templatemonster.com/screenshots/21000/21000-z-b.jpg</uri>
  <filemtime>2008-08-28 08:08:203</filemtime>
  <main_preview>1</main_preview>
</screenshot>
<screenshot>
  <uri>http://images.templatemonster.com/screenshots/21000/21000-z-html.html</uri>
  <filemtime>2008-08-28 08:08:20</filemtime>
</screenshot>
</screenshots_list>
<keywords>photo video store online shop camera products electronics portable monitor o
<styles>
  <style>
    <style_id>16</style_id>
    <style_name>Neutral</style_name>
  </style>
</styles>
<categories>
  <category>
    <category_id>13</category_id>
    <category_name>Neutral</category_name>
  </category>
  <category>
    <category_id>40</category_id>
    <category_name>Art Photography</category_name>
  </category>
  <category>
    <category_id>42</category_id>
    <category_name>Online store/shop</category_name>
  </category>
  <category>
    <category_id>50</category_id>
    <category_name>Electronics</category_name>
  </category>
  <category>
    <category_id>78</category_id>
    <category_name>Zero Downloads</category_name>
  </category>
  <category>
    <category_id>110</category_id>
    <category_name>Zen cart Templates</category_name>
  </category>
</categories>
<sources_available_list>
  <source>
    <source_id>3</source_id>
  </source>
  <source>
    <source_id>12</source_id>
  </source>
</sources_available_list>
<sources>.PSD; &lt;br> .PHP</sources>
<description></description>
<software_required_list>
  <software>
    <software_id>29</software_id>
  </software>
  <software>
    <software_id>30</software_id>
  </software>
  <software>
    <software_id>64</software_id>
  </software>
  <software>
    <software_id>8</software_id>
  </software>
</software_required_list>
```

```

</software>
<software>
  <software_id>26</software_id>
</software>
<software>
  <software_id>53</software_id>
</software>
</software_required_list>
<software_required>PHP 4.3.2 or higher (PHP 4.4.x for optimal performance); Apache 1.3.3.7
<pages>
  <page>
    <name>Main</name>
    <screenshots>
      <scr>
        <description>REAL SIZE SCREENSHOT</description>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-rs.jpg</uri>
        <scr_type_id>0</scr_type_id>
        <width>0</width>
        <height>0</height>
        <href></href>
      </scr>
      <scr>
        <description/>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-z-html.html</uri>
        <scr_type_id>127</scr_type_id>
        <width>430</width>
        <height>60</height>
        <href></href>
      </scr>
      <scr>
        <description>Zen-cart Main page preview</description>
        <uri>http://images.templatemonster.com/screenshots/21000/21000-z-b.jpg</uri>
        <scr_type_id>122</scr_type_id>
        <width>430</width>
        <height>586</height>
        <href></href>
      </scr>
    </screenshots>
  </page>
</pages>
</template>
</templates>

```

## 4.2. template\_updates.php.

The script allows to download complete information about templates that were updated during a certain period.

### URL:

[http://www.templatemonster.com/webapi/template\\_updates.php](http://www.templatemonster.com/webapi/template_updates.php)

### Description:

Returns XML with information about templates that were updated during a certain period.

### Status:

0.1

### Synopsis:

[http://www.templatemonster.com/webapi/template\\_updates.php?from=<from\\_date\\_time>&to=<to\\_date\\_time>](http://www.templatemonster.com/webapi/template_updates.php?from=<from_date_time>&to=<to_date_time>)

### Parameters:

Parameter	Type	Description
from	date & time (19 chars length)	Date & time in "YYYY-MM-DD hh:mm:ss" format
to	date & time ( 19 chars length)	Date & time in "YYYY-MM-DD hh:mm:ss" format

**Response:**

XML file contains an XML-encoded array. The array consists of the following arrays:

Field	Type	Description
id	integer	an item number of the template
state	integer	equals 0 for hidden templates. Equals 1 for visible templates. Equals 2 for exclusively sold templates.
price	integer	a regular price of the template (in USD)
exc_price	integer	an exclusive price of the template (in USD)
inserted_date	date	date of addition in YYYY-MM-DD format
downloads	integer	the number of downloads
template_type	string	a type of the template
update_date	date	The date of the latest update in the format YYYY-MM-DD hh:mm:ss
is_flash	integer (1/0) 1-true	1 for Flash Intro templates
is_adult	integer (1/0) 1-true	1 for Adult templates
<width>980px</width>		Width of the template in pixels
sources_available_list	array	The list of IDs corresponding to the node <sources></sources> of the directories archive t_info_dir.zip. The list contains IDs of the source formats included into redistributable package of the template.
screenshots_list	array	An array of all the screenshots and time of the screenshot modification. Full URL is displayed. Contains small_preview and main_preview arrays that have the 1 value for the screenshots of the small template preview and main template preview (the image showing on roll-over) accordingly.
software_required_list	array	The list of IDs corresponding to the node <softwares></softwares> of the directories archive t_info_dir.zip. The list contains IDs of the software needed for editing and changing sources of the tem-

Field	Type	Description
		plate.
author	integer	a template author
packages	int	The number of the package to which the template belongs.
is_full_site	integer (1/0) 1-true	1 for Full Site templates
is_real_size	integer (1/0) 1-true	1 if a "Real Size" screenshot exists
screenshots_list	array	an array of all screenshots and screenshots file modification time. Full URL is displayed.
keywords	string	a list of all keywords associated with a particular template (space separated).
styles	array	an array of all styles of a particular template
categories	array	an array of all categories of a particular template
sources	string	information about sources available for this template( deprecated).
description	string	a description of the template.
software_required	string	a software required for editing the template (deprecated).
pages	array	an array of all pages of the template. Each page consists of the name of the page and the list of screenshots. Each screenshot consists of the screenshot name and the URL. Full URL is displayed.

**Response example:**

ht-  
 tp://www.templatemonster.com/webapi/template\_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86

**4.3. template\_xml.php.**

Receive full template info in xml format by the template number.

**URL:**

[http://www.templatemonster.com/webapi/template\\_xml.php](http://www.templatemonster.com/webapi/template_xml.php)

**Description:**

Returns xml with the info about the requested template- template\_number.

**Synopsis:**

[http://www.templatemonster.com/webapi/template\\_xml.php?template\\_number=<template\\_number>](http://www.templatemonster.com/webapi/template_xml.php?template_number=<template_number>)

**Parameters:**

Parameter	Type	Description
template_number	integer	Template number

**Response:**

XML file contains an XML-encoded array. The response format is similar to `template_updates.php` and `t_info.xml`.

**4.4. t\_info\_dir.zip.**

Directories Archive.

**URL:**

[http://www.templatemonster.com/webapi/xml/t\\_info\\_dir.zip](http://www.templatemonster.com/webapi/xml/t_info_dir.zip)

**Description:**

Download full info about directories in XML format. Contains sources, softwares, categories and authors notes packed into .zip archive.

**Synopsis:**

[http://www.templatemonster.com/webapi/xml/t\\_info\\_dir.zip](http://www.templatemonster.com/webapi/xml/t_info_dir.zip)

**Parameters:**

No

**Response:**

Field	Type	Description
sources	array	List of sources included with the template, value-name pairs format.
softwares	array	List of software required for template customization, value-name pairs format.
categories	array	List of template categories, value-name pairs format.
authors	array	List of the template authors, value-name pairs format.
packages	array	List of the packages that templates belong to, value-name pairs format.

**Response example:**

ht-

[tp://www.templatemonster.com/webapi/template\\_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86](http://www.templatemonster.com/webapi/template_updates.php?from=2005-07-16%2022:00:00&to=2005-07-17%2000:00:00&login=kara&webapipassword=23kikhuh8656io62549hjsdguwtre86)

```
<?xml version="1.0" encoding="utf-8"?>
  <directories>
    <sources>
      <source>
        <id>2</id>
        <name> .HTML</name>
```

```
</source>
</sources>
<softwares>
  <software>
    <id>8</id>
    <name> Adobe Photoshop CS+</name>
  </software>
</softwares>
<categories>
  <category>
    <id>1</id>
    <name>Beauty</name>
  </category>
</categories>
<authors>
  <author>
    <id>135</id>
    <name>Adonis</name>
  </author>
</authors>
<packages>
  <package>
    <id>141</id>
    <name>WordPress 2.6</name>
  </package>
</packages>
</directories>
```

---

# Chapter 3. Versions History

**2005/08/04**

- *styles.php* script was added
- *template\_styles.php* script was added
- *currency.php* script was added

**2006/06/25**

- *template\_xml.php* script was added
- *t\_info\_dir.zip* was added
- *template\_updates.php* script was updated
- *t\_info.zip* was updated

**2004/09/29**

- *locales* parameter was added to *categories.php* script
- *currency* parameter was added to *templates\_screenshots4.php* script

**2004/07/12**

- XML API was updated

**2004/05/07**

- *templates\_updates.php* script was added
- *xml/t\_info.zip* was added

**2004/04/07**

- *template\_info.php* script was added

**2003/12/29**

- *templates\_screenshots4.php* script was added
- *templates\_screenshots3.php* script was deprecated

**2003/08/28**

- *templates\_screenshots3.php* script was added
- *templates\_screenshots2.php* script was deprecated

**2003/05/29**

- *templates\_screenshots2.php* script was added
- *templates.php* and *templates\_screenshots.php* scripts were deprecated

**2003/04/17**

- *featured.php* script was added

**2003/04/16**

- *templates.php* - new parameter *category*
- *templates.php* - new parameter *sort\_by*
- *templates.php* - new parameter *order*
- *templates\_screenshots.php* script was added

**2003/04/15**

- *templates.php* - new parameter *filter*

---

# Chapter 4. Appendix.

## 1. Useful Links.

<http://www.template-help.com/> - Unbranded Help Center

<http://www.template-help.com/kb> - Knowledgebase

<http://www.template-help.com/tickets> - Submit a Support Ticket

<http://www.template-help.com/samples> - Sample Templates

<http://www.template-help.com/library> - Clipart Library

<http://www.template-help.com/chat> - Support Chat

## 2. Links to the Shopping Cart

**URL:** <http://www.templatehelp.com/preset/cart.php>

**Description:** A shopping cart script. You should use parameters specified in the synopsis for <http://www.templatehelp.com/preset/cart.php> to let your visitors select and purchase templates, review what they have selected, make necessary modifications or additions to their shopping carts. You should create a preset in the Mytemplatestorage.com affiliate account to get a unique preset identifier (code). Refer to Mytemplatestorage.com User Guide for more detailed information on how to create and manage presets.

**Synopsis:** [http://www.templatehelp.com/preset/cart.php?pr\\_code=<pr\\_code>&act=<action>&templ=<template\\_number1>%20<template\\_number2>%20<template\\_number3>](http://www.templatehelp.com/preset/cart.php?pr_code=<pr_code>&act=<action>&templ=<template_number1>%20<template_number2>%20<template_number3>)

**Parameters:**

Parameter	Type	Description
pr_code	string (30 chars length)	Your MyTemplateStorage preset identifier
act	string	A parameter that allows to manage a shopping cart. Acceptable values: <ul style="list-style-type: none"><li>• <i>add</i> - to add a particular template to the shopping cart</li><li>• <i>empty</i> - to empty the shopping cart (delete all items from the shopping cart)</li><li>• <i>del</i> - to delete a particular item (template) from the shopping cart.</li></ul>
templ	list of space separated integers	item number(s) of the template

**Example:** To add a template #9000 to the shopping cart you need to use the following script URL: [http://www.templatehelp.com/preset/cart.php?pr\\_code=9000&act=add&templ=9000](http://www.templatehelp.com/preset/cart.php?pr_code=9000&act=add&templ=9000)

[tp://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=9000](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=9000)

To delete a template #9000 from the shopping cart you need to use the following script URL: [http://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=9000](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=9000)

To empty a shopping cart (delete all items from the shopping cart) you need to use the following script URL: [http://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=empty](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=empty)

To add several templates (#8541, 9632, 1, 4555, and 8523) to the shopping cart you need to use the following script URL:

[ht-tp://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=8541%209632%201%204555%208523](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=add&templ=8541%209632%201%204555%208523)

To delete several templates (#8541, 9632) from the shopping cart you need to use the following script URL:

[ht-tp://www.templatehelp.com/preset/cart.php?pr\\_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=8541%209632](http://www.templatehelp.com/preset/cart.php?pr_code=xxxxxxxxxxxxxxxxxxxxxxxxxxxx&act=del&templ=8541%209632)

where xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx is your unique preset identifier (code).

### 3. Links to Templatetuning.com

If you wish to include a link to Templatetuning.com at your template shop use the following URL to let your visitors navigate to the main page of Templatetuning.com - [http://www.template-help.com/tuning/tuning.php?aff=<affiliate\\_username>](http://www.template-help.com/tuning/tuning.php?aff=<affiliate_username>)

or the following URL to let your visitors navigate to the registration page with a particular template selected - [http://www.template-help.com/tuning/tuning.php?aff=<affiliate\\_username>&t\\_number=<template\\_number>](http://www.template-help.com/tuning/tuning.php?aff=<affiliate_username>&t_number=<template_number>)

where '*affiliate\_username*' is your affiliate username; '*template\_number*' is an item number of the template.

## Glossary

### Glossary

API

Historically, "application programming interface". Practically, an API is any interface that enables one program to use facilities provided by another, whether by calling that program, or by being called by it. At a higher level still, an API is a set of functionality delivered by a programming system, and as such the mix of APIs in a particular system tells you what that system can do. <http://en.wikipedia.org/wiki/API>

ASP

A server-side technology developed by Microsoft [<http://www.microsoft.com/>] for dynamically-generated web pages that is marketed as an add-on to Internet Information Services (IIS [<http://www.microsoft.com/WindowsServer2003/iis/default.msp>]). [www.asp.net](http://www.asp.net) [<http://www.asp.net/>]

Coldfusion

A tag-based, middleware programming language used chiefly for writing web-based applications. [www.macromedia.com/software/coldfusion/](http://www.macromedia.com/software/coldfusion/) [<http://www.macromedia.com/software/coldfusion/>]

database

A collection of information stored in a computer in a systematic way, such that a computer program can consult it to answer questions.

delimiter	A sequence of characters used to separate the columns.
float	A type of data for storing numbers with decimal digits.
HTTP	Hyper Text Transfer Protocol; the World Wide Web protocol that performs the request and retrieve functions of a server. Commonly seen as the first part of a website address. <a href="http://www.w3.org/Protocols">www.w3.org/Protocols</a> [ <a href="http://www.w3.org/Protocols/">http://www.w3.org/Protocols/</a> ]
integer	A positive, negative or equal to zero number without a fractional part.
linebreak	A sequence of characters used to separate the lines.
Perl	Practical Extraction and Reporting Language is an open source server side programming language extensively used for web scripts and to process data passed via the Common Gateway Interface from HTML forms etc. Perl scripts are not embedded within HTML [ <a href="http://www.w3.org/MarkUp/">http://www.w3.org/MarkUp/</a> ] pages and do not download to the web browser but reside on the server. <a href="http://www.perl.com">www.perl.com</a> [ <a href="http://www.perl.com/">http://www.perl.com/</a> ]
PHP	Hypertext Preprocessor; an open source, server-side HTML [ <a href="http://www.w3.org/MarkUp/">http://www.w3.org/MarkUp/</a> ] scripting language used to create dynamic Web pages. PHP is embedded within tags, so the author can move between HTML and PHP instead of using large amounts of code. Because PHP is executed on the server, the viewer cannot see the code. PHP can perform the same tasks as a CGI [ <a href="http://hoohoo.ncsa.uiuc.edu/cgi/">http://hoohoo.ncsa.uiuc.edu/cgi/</a> ] program can do and is compatible with many different kinds of databases. <a href="http://www.php.net">www.php.net</a> [ <a href="http://www.php.net/">http://www.php.net/</a> ]
plain text	Text encoded in the ASCII [ <a href="http://en.wikipedia.org/wiki/ASCII">http://en.wikipedia.org/wiki/ASCII</a> ] format. As such, it is software independent and can be imported, read, and exported by virtually every software application.
protocol	On the Internet "protocol" usually refers to a set of rules that define an exact format for communication between systems. For example the HTTP protocol defines the format for communication between web browsers and web servers, the IMAP [ <a href="http://www.imap.org/">http://www.imap.org/</a> ] protocol defines the format for communication between IMAP email servers and clients, and the SSL [ <a href="http://www.openssl.org/">http://www.openssl.org/</a> ] protocol defines a format for encrypted communications over the Internet.
script	A set of commands written in an interpreted language to automate certain application tasks.
script response	Message of script that is returned to a sender.
shopping cart	A piece of software that acts as an online store's catalog and ordering process. Typically, a shopping cart is the interface between a company's Web site and its deeper infrastructure, allowing consumers to select merchandise; review what they have selected; make necessary modifications or additions; and purchase the merchandise.
string	A linear sequence of symbols (characters or words or phrases).
synopsis	

A wrapper for command or function syntax.

WebAPI

An analog of the API for websites.

XML

Extensible Markup Language; a standard for creating markup languages which describe the structure of data. It is not a fixed set of elements like HTML [<http://www.w3.org/MarkUp/>], but rather, it is like SGML [<http://www.w3.org/MarkUp/SGML/>] (Standard Generalized Markup Language) in that it is a metalanguage, or a language for describing languages. XML enables authors to define their own tags. [www.w3.org/XML](http://www.w3.org/XML/) [<http://www.w3.org/XML/>]